



## SPECIFICATION

MODEL	LK-B20(LK-B21)	LK-B230
PRINTING METHOD	Thermal Transfer and Direct Thermal	
PRINTING SPEED	Up to 152mm/sec	Up to 102mm/sec
PRINT WIDTH	104mm(4.1")	
PRINT LENGTH	1250mm(49.2")	650mm (25.5")
RESOLUTION	203DPI(8 dots/mm)	
PAPER WIDTH (min-max)	18mm ~ 118mm(0.7" ~ 4.64")	
PAPER ROLL SIZE (min-max)	Internal : Ø 25.4(1") ~ Ø 127mm(5.0") External : Ø 38.1(1.5") ~ Ø 200mm(7.8")	
PAPER THICKNESS	0.06mm ~ 0.20mm	
PAPER TYPE	Label, Tag, Continuous, Fanfold	
PAPER SENSOR	Label Gap Sensor, Notch Sensor, Black Mark Sensor	
INTERFACE	STANDARD	USB, Parallel(IEEE-1284)
	OPTION	Serial(RS-232C), Ethernet, Wi-Fi 802.11b/g
RIBBON WIDTH	33mm ~ 110mm(1.3 ~ 4.3")	
RIBBON LENGTH	360M, Ø 67mm(2.5")	
MEMORY	STANDARD	8MB SDRAM, 5MB Flash
	OPTION	16MB Flash
BARCODE	1D	Code39, Code128 with subsets A/B/C, Code93, Codabar, Interleaved 2 of 5, UPC-A and UPC-E with 2 or 5 digit extensions, EAN-8 and EAN-13 with 2 or 5 digit extensions, Postnet, Plessey, German Post Code, MSI-3, UCC/EAN-128
	2D	Aztec Code, PDF 417, QR Code, DataMatrix, MaxiCode (EPL II and ZPL II), Code 49 (ZPL II)
FONT SPECIFICATION		6 bitmapped - 8x12, 10x16, 12x20, 14x24, 32x48, 24x24(KSC5601)
		7 bitmapped - 5x9, 7x11, 10x18, 15x28, 13x26, 40x60, 13x21
		1 smooth scalable
DRIVER	Windows Printer Driver(7, XP, 2000, 2003, 2008, Vista (32 & 64 bit))	
POWER	AC 100-240V, 24VDC, 2.5A	AC100-240V, 24VDC, 2.92A
DIMENSIONS	215mm x 287mm x 231mm	
WEIGHT(KG)	3.6KG	

## DESKTOP BARCODE LABEL PRINTING

# LK-B20/B230

- Thermal transfer and Direct thermal printing
- Stable and reliable label printing
- High capacity memory
- Large capacity of roll (200mm OD) with external media holder
- Less ribbon replacement with 360M length (Wax, Wax/Resin, Resin)
- Paper width adjustable from 18mm to 118mm
- Selectable optional auto cutter or peeler



◀ INTERFACE  
Standard interface card  
- USB  
- Parallel(IEEE-1284)  
Optional interface card  
- Serial(RS-232C), Ethernet,  
Wi-Fi 802.11b/g



◀ Peeler



◀ Auto cutter

## APPLICATION

